

Technical Data Sheet

ROOF Protect PES 220



Product description:

The ROOF Protect PES 220 is a vapor permeable underlay membrane consisting of polyester fleece with multiple special coatings. It can be used as an underlay, formwork and on wooden formwork as well as thermal insulation. A special property is the protection against perforation, which has been proven by ETA-18/O292 and the TU Berlin.

ROOF Protect PES 220

application	underlay membrane		
functional layer	acrylate special coating		
carrier material	polyester fleece		
color of carrier material	anthracite		
basis weight	EN 1849-2	g/m ²	220 (± 20)

PROPERTY	TEST	UNIT	VALUE
----------	------	------	-------

General characteristics

roll width	EN 1848-2	m	1,5
roll length	EN 1848-2	m	50
m ² per roll	EN 1848-2	m ²	75
roll weight	-	kg	16,5
rolls per pallet	-	rolls	24

Technical characteristics

dimensional accuracy	EN 1107-2	%	< 1
thickness	EN 1849-2	mm	-
behavior in case of fire	EN 13501-1	class	E
resistance to water penetration	EN 1928	class	W1
after artificial aging	EN 1297/1296	class	W1
maximum tensile force MD/CD	EN 12311-1	N/50 mm	350 / 260
maximum tensile force after aging MD/CD	EN 12311-1	N/50 mm	350 / 250
elongation MD/CD	EN 12311-1	%	30 / 60
elongation after aging MD/CD	EN 1297/1296	%	25 / 60
tear resistance / nail shaft MD/CD	EN 12310-1	N/200 mm	135 / 185
cold bending behavior	EN 1109	°C	≤ -30
diffusion-equivalent air layer thickness	EN ISO 12572	sd-value-m	0,1
resistance to air passage	EN 12114	m ³ /(m ² /h/50Pa)	0
temperature resistance	EN 13859-1	°C	-40 to +100
outdoor exposure time	-	months	3
UV resistance	-	-	permanent
resistance to driving rain	TU-Berlin	-	passed - AZ 141203
suitability as a material for temporary cover	-	months	3
ZVDH product data sheet - class	-	-	UDB-A / USB-A
Ö-Norm: B3661 - Table 5/4119 - Section 6.1.2	-	-	Type II

The values may be subject to tolerances. If nothing is specified, the tolerance customary in the industry applies according to the standard, material and property.

