

## Technical Data Sheet

# ROOF Protect PES 270



### ***Product description:***

The ROOF Protect PES 270 is a vapor-permeable underlay consisting of polyester fleece with multiple special coatings. It can be used as an underlay, formwork and on wooden formwork as well as thermal insulation. A special property is the protection against perforation, which has been proven by ETA-18/0292 and the TU Berlin.

# ROOF Protect PES 270

application	underlay membrane		
functional layer	acrylate special coating		
carrier material	polyester fleece		
color of carrier material	anthracite		
basis weight	EN 1849-2	g/m <sup>2</sup>	270 (± 10)

PROPERTY	TEST	UNIT	VALUE
----------	------	------	-------

## General characteristics

roll width	EN 1848-2	m	1,5
roll length	EN 1848-2	m	50
m <sup>2</sup> per roll	EN 1848-2	m <sup>2</sup>	75
roll weight	-	kg	20,25
rolls per pallet	-	rolls	12

## Technical characteristics

dimensional accuracy	EN 1107-2	%	< 1
thickness	EN 1849-2	mm	1,15
behavior in case of fire	EN 13501-1	class	E
resistance to water penetration	EN 1928	class	W1
after artificial aging	EN 1297/1296	class	W1
maximum tensile force MD/CD	EN 12311-1	N/50 mm	500 / 390
elongation MD/CD	EN 12311-1	%	35 / 50
tear resistance / nail shaft MD/CD	EN 12310-1	N/200 mm	200 / 250
cold bending behavior	EN 1109	°C	-40
diffusion-equivalent air layer thickness	EN ISO 12572	sd-value-m	0,1
resistance to air passage	EN 12114	m <sup>3</sup> /(m <sup>2</sup> /h/50Pa)	≤ 0,1
temperature resistance	EN13859-1	°C	-40 to +160
outdoor exposure time	-	months	3
UV resistance	-	-	permanent
resistance to driving rain	TU-Berlin	-	passed
suitability as a material for temporary cover	-	months	3
ZVDH product data sheet - class	-	-	UDB-A / USB-A
Ö-Norm: B3661 - Table 5/4119 - Section 6.1.2	-	-	Type II

The values may be subject to tolerances. If nothing is specified, the tolerance customary in the industry applies according to the standard, material and property.

