

# Technical Data Sheet

## SWISSTAPE 3700 Construction time sealing

### Product description:

The full-surface self-adhesive, rainproof construction seal protects the wooden elements before and during the construction phase.



### Product properties

- anti-slip
- self-adhesive
- waterproof
- translucent
- divided liner at 150 mm (with roll width 300 mm)

### Packaging Unit

- 300 mm      25 rolls / pallet
- 1550 mm    20 rolls / pallet

### Technical specifications

PROPERTY	VALUE	TEST
carrier system	polypropylene fleece with special coating	
adhesive	modified dispersion acrylate	
cover	plastic liner	
roll width	300 mm (150/150), 1550 mm	
roll length	50 lfm	
basis weight	200 g/m <sup>2</sup>	DIN EN 1849-2
processing temperature	-5 °C to +40 °C	
temperature resistance	-40 °C to +80 °C	
sd value	6 m (± 1 m)	DIN EN 1931
resistance to water passage	W1	DIN EN 1928
fire class	class E	
outdoor exposure	4 months	
storage	cool and dry	
prerequisite for secure bonding	The substrate must be dry, closed, level, stable, free of dust and grease and must not be adhesive-repellent. Before gluing, the substrates must be cleaned and adhesion tests carried out.	

The values may be subject to tolerances. If nothing is specified, the tolerance customary in the industry applies according to the standard, material and property.

