

Technical Data Sheet

SWISSTAPE 3735

Product description:

SWISSTAPE 3735 is a window connection tape for indoor use. The special fleece composite with an sd value of 22 m enables an airtight connection between the window and the brickwork.



Product properties

- fully adhesive
- plasterable
- split liner at 15mm
- airtight

Packaging unit

75 mm	8 rolls / box
100 mm	6 rolls / box
150 mm	4 rolls / box

Technical specifications

PROPERTY	VALUE	TEST
carrier system	diffusion-tight special fleece	
adhesive	modified dispersion acrylate	
adhesive application	260 g/m ²	DIN EN 1849-2
cover	foil liner white	
roll width	75 mm, 100 mm, 150 mm	
roll length	25 lfm	
peel strength	fulfills	DIN 4108-11
processing temperature	-5 °C to +40 °C	
temperature resistance	-40 °C to +100 °C	
sd value	22 m (± 1 m)	DIN EN 1931
storage	cool and dry	
prerequisite for secure bonding	The substrate must be dry, closed, level, stable, free of dust and grease and must not be adhesive-repellent. Before gluing, the substrates must be cleaned and adhesion tests carried out.	

The values may be subject to tolerances. If nothing is specified, the tolerance customary in the industry applies according to the standard, material and property.

